A modern interior space with a glass partition and a chair. The room features a dark, textured floor and walls. A glass partition with a grid of small circular fasteners is visible. A white chair is positioned on the left side of the frame. The text "FritsJurgens®" and "TECHNICAL DOCUMENTATION" is overlaid on the right side of the image.

FritsJurgens®

TECHNICAL DOCUMENTATION

INDEX

01

Why FritsJurgens

[Invisible perfection](#)
[Unlimited design](#)
[Motion technology](#)
[Timeless quality](#)

05

System M+

[Specifications](#)
[Movement](#)
[Technical drawing](#)
[Design options](#)
[Model selector](#)

Downloads

[System M32+ 2D drawing](#)
[System M32+ 3D drawing](#)
[System M32+ BIM model](#)
[System M42+ 2D drawing](#)
[System M42+ 3D drawing](#)
[System M42+ BIM model](#)

02

Door specifications

[8 mm into the floor, 18 mm into the ceiling](#)
[Gaps around the door](#)
[Min. 40 mm door thickness](#)
[Doors between 20 - 500 kg](#)
[Pressure load](#)
[Lateral force](#)

06

System M

[Specifications](#)
[Movement](#)
[Technical drawing](#)
[Design options](#)
[Model selector](#)

Downloads

[System M 2D drawing](#)
[System M 3D drawing](#)
[System M BIM model](#)

03

System Specification

[Positioning of the systems](#)
[Compare all systems](#)
[Functions](#)
[Movement](#)

07

System 3

[Specifications](#)
[Technical drawing](#)
[Model selector](#)

Downloads

[System 3 2D drawing](#)
[System 3 3D drawing](#)
[System 3 BIM model](#)

04

Accessories

[Top pivot - Cable Grommet](#)
[Flush](#)
[Hexagon Guide](#)
[Axle Wrench](#)



08

System One

[Specifications](#)
[Technical drawing](#)

Downloads

[System One 2D drawing](#)
[System One 3D drawing](#)
[System One BIM model](#)



INVISIBLE PERFECTION


The pivot hinge systems by FritsJurgens are unique while there are no structural elements necessary in the floor and the ceiling. The system components are fully-mortised in the bottom and top of the door. Only surface-mounted floor and ceiling plates need to be installed, making the system virtually invisible. All the attention goes where it is supposed to go – to the design of the pivot door and its surroundings.



UNLIMITED DESIGN

As a professional, you want to create more than just a door. You want to create a design statement. With a FritsJurgens pivot hinge design possibilities are unlimited and, the movement of the door is fluent, whether your door weighs 20 kg or 500 kg.

FritsJurgens pivot hinges are ideal for all kinds of pivot doors – large or small, light or heavy, interior or exterior. Whether in residential or commercial environments, almost any material is possible for your pivot door.



MOTION TECHNOLOGY

Power becomes control

Why constrain power when you can convert it into control? Motion technology puts hydraulic power to use by turning it into a controlled, smooth door movement. This is what makes motion technology unique. In System M and System M+ the movement of the pivot door is created and controlled by motion technology. In heavy and light doors. Unabridged power, full control.




TIMELESS QUALITY

FritsJurgens pivot hinges are virtually indestructible. Built from high-performance materials, the systems are maintenance-free.

Our rigorous testing shows that even after 1 million cycles our systems continue to perform as they were designed, perfectly balancing technology, quality, and aesthetics.




8 MM INTO THE FLOOR, 18 MM INTO THE CEILING



The top pivot and bottom pivot hinge system components are fully-mortised in the pivot door. Only small floor and ceiling plates are visible. The floor plate fasteners only need to be mortised 8 mm into the floor, which means every FritsJurgens system can also be utilized in combination with radiant floor heating.


GAPS AROUND THE DOOR

www.fritsjurgens.com/gap


GAP LEFT (1) AND RIGHT (2)

Example for minimum gaps between the door and the wall or jamb:

X	Door thickness	40 mm
A	Distance of pivot point to end of the door	1500 mm
B	Distance pivot point to beginning door	91 mm
1	Minimum gap between door and wall	4 mm
2	Minimum gap between door and wall	2 mm



B	1			
2000	2	2	2	2
1500	2	2	2	2
1000	2	2	3	3
500	2	3	3	3
250	3	3	4	4
91	4	5	7	9
X ▶	40	50	60	70



A	2			
2000	2	2	2	2
1500	2	2	2	2
1000	2	2	3	3
500	2	3	3	3
250	3	3	4	4
91	4	5	7	9
X ▶	40	50	60	70

When $X > 70$ mm, please go to the online gap calculation tool on top of this page. Dimensions in mm. Based on straight angles. The dimensions are indicative. No rights can be derived from it.

BOTTOM GAP: 11 (M+/M) 13 MM (3/ONE)

The minimum gap at the side of the door depends on the thickness (X) and the width of the door in relation to the positioning of the hinge (A and B). Important: the minimum distance from the pivot point of the hinge to the edge of the door (A) is 91 mm. There is no need to add extra space for installing (2 mm tolerance is included).

MINIMUM DOOR THICKNESS 40 MM




Since the FritsJurgens pivot hinges have a thickness of 32 mm (or 42 mm) they can be used in doors with a minimum thickness of 40 mm. This makes FritsJurgens systems suitable for doors of virtually any size and material, giving designers the freedom to design the ultimate pivot door.

SUITABLE FOR DOORS BETWEEN 20 - 500 KG

SYSTEM RANGE

System M+	20-500 kg
System M	20-210 kg
System 3	40-350 kg
System One	20-500 kg



Each FritsJurgens pivot system is suitable for light and heavy doors. System M+ comes in models tuned for doors from 20 up to 500 kg. System M is suitable for door between 20 and 210 kg. System One also supports doors up to 500 kg, while System 3 supports doors from 40 to 350 kg. The possibilities for the design of the door are endless and the movement is smooth and fluent.

POSITIONING OF THE SYSTEMS

www.fritsjurgens.com/tools



SIDE PLACEMENT

System M+

System M

System One



MIDDLE PLACEMENT

System 3

System One

FritsJurgens pivot hinge systems can be used to design pivot doors with side and middle placement. Depending on the positioning of the system and the function of the pivot door, the right system can be selected.

COMPARE SYSTEMS

	SYSTEM M+	SYSTEM M	SYSTEM 3	SYSTEM ONE
System features	M32+: 294,8 x 32 x 99,6 mm M32+: 2,6 KG M42+: 308,2 x 42 x 112,7 mm M42+: 3,6 KG	294,8 x 32 x 99,6 mm 2,6 KG	160 x 32 x 143 mm 0,75 KG	160 x 32 x 39 mm 0,36 KG
Material	Stainless Steel Anodized aluminum	Stainless Steel Anodized aluminum	Stainless Steel Anodized aluminum	Stainless Steel Anodized aluminum
Corrosion resistance	EN 1670 - class 5 (norm:o-5)	EN 1670 - class 5 (norm:o-5)	EN 1670 - class 5 (norm:o-5)	EN 1670 - class 5 (norm:o-5)
Door features	Double-acting 180° rotation Single-acting 90° rotation	Double-acting 180° rotation Single-acting 90° rotation	Double-acting 360° rotation	Double-acting 360° rotation Single-acting 90° rotation
Hold positioning	Hold positions 90°, -90° and 0°	Hold positions 90°, -90° and 0°	Hold positions 0°, 90°, 180°, 270°	360° free-swinging pivot
Weight capacity	20-500 KG	20-210 KG	40-350 KG	20-500 KG
Door width	400-5000 mm	400-4400 mm	1000-3800 mm	Unlimited
Door height	Unlimited	Unlimited	Unlimited	Unlimited
Pivot point	Min. 91 mm to short side	Min. 91 mm to short side	Min. 91 mm to short side	Min. 91 mm to short side
Door thickness	M32+: 40 mm M42+: 50 mm	40 mm	40 mm	40 mm
Door movement	Self-closing from 125° and -125° to 0° 1. Damper Control Back-check for damping on opening, soft-close. 2. 30° Speed Control Adjustable closing speed in last part of closing. L Latch Control Accelerates the door shortly before closed position.	Self-closing from 125° and -125° to 0° 1. Damper Control Back-check for damping on opening, soft-close.	Door moves from each 45° angle, in both directions, to a hold position.	360° free-swinging pivot
	GO TO SYSTEM M+	GO TO SYSTEM M	GO TO SYSTEM 3	GO TO SYSTEM ONE

FritsJurgens offers four series of pivot hinges, creating a solution for every pivot door. Every pivot hinge is fully mortised in the pivot door and easy to install.

FUNCTIONS


SYSTEM M+

Double-acting doors

Rotation 180°

Hold positions 90°, -90° and 0°

Self-closing from 125° and -125° to 0°




Single-acting doors (with door frames*)

Rotation 90°

Hold positions 90° and 0°

Self-closing from 125° to 0°



**Due to Latch Control (see next page)*


SYSTEM M

Double-acting doors

Rotation 180°

Hold positions 90°, -90° and 0°

Self-closing from 125° and -125° to 0°




Single-acting doors

Rotation 90°

Hold positions 90° and 0°

Self-closing from 125° to 0°




SYSTEM 3

Double-acting doors

Rotation 360°


Hold positions 0°, 90°, 180°, 270°



SYSTEM ONE


Double-acting doors

Rotation 360°



Single-acting doors

Rotation 90°




When the pivot hinge is placed on the left or right side of the door, allowing 90° rotation or 180° rotation, System M+, System M and System One are suitable choices. When the pivot hinge is placed in the middle of the door this will allow for 360° rotation. Both System 3 and System One are suitable choices.

MOVEMENT

SYSTEM M+ | SELF-CLOSING FROM 125° AND -125° TO 0°


1. Damper Control

Back-check for damping on opening, soft-close.




2. 30° Speed Control

Adjustable closing speed in last part of closing movement.



L Latch Control


Accelerates the door shortly before closed position to ensure proper latching.



SYSTEM M | SELF-CLOSING FROM 125° AND -125° TO 0°


1. Damper Control

Back check for damping on opening, soft-close.




SYSTEM 3

Door moves from each 45° angle, in both directions, to a hold position.



SYSTEM ONE

360° free-swinging pivot.



In System M and System M+ the movement of the pivot door is generated and controlled by motion technology. Motion technology puts hydraulic power to use by turning it into a controlled, smooth door movement. This is what makes motion technology unique. System 3 can rotate 360° and is characterized by a hold position at every quarter of the circle. System One is the most compact system: the hinge acts as a revolving point.

FRITSJURGENS SYSTEM M+/M



SYSTEM M+

SYSTEM SPECIFICATIONS

Types	M32+ SCA	
	M32+ SCB	
	M32+ SCC	
	M32+ SCD	
	M32+ SCE	
		M42+ SCF
		M42+ SCG
Dimensions	M32+ 294,8 x 32 x 99,6 mm	M42+ 308,2 x 42 x 112,7 mm
Weight	2,6 KG	3,6 KG
Material	Stainless Steel Anodized aluminum	
Corrosion resistance	EN 1670 - class 5 (norm:0-5)	

DOOR SPECIFICATIONS

Door acting	Double-acting 180° rotation	
	Single-acting 90° rotation with door frames*	
	<i>*Due to Latch Control (see previous page)</i>	
Hold positioning	Hold positions 90°, -90° and 0°	
Weight capacity	20-500 KG	
Door width	400 - 5000 mm	
Door height	Unlimited	
Pivot point	Min. 91 mm from pivot point to short side	
Min. door thickness	M32+ 40 mm	M42+ 50 mm

DOOR MOVEMENT

Door movement	Self-closing from 125° and -125° to 0°	
	Damper Control - Back-check for damping on opening, soft-close.	
	30° Speed Control - Adjustable closing speed in last part of closing.	
	Latch Control - Accelerates the door shortly before closed position.	

All controls can be individually adjusted from the bottom of the door.

SYSTEM M

SYSTEM SPECIFICATIONS

Types	M32 SCAA
	M32 SCA
	M32 SCB
	M32 SCC
Dimensions	294,8 x 32 x 99,6 mm
Weight	2,6 KG
Material	Stainless Steel Anodized aluminum
Corrosion resistance	EN 1670 - class 5 (norm:0-5)

DOOR SPECIFICATIONS


Door acting	Double-acting 180° rotation	
	Single-acting 90° rotation	
Hold positioning	Hold positions 90°, -90° and 0°	
Weight capacity	20-210 KG	
Door width	400 - 4400 mm	
Door height	Unlimited	
Pivot point	Min. 91 mm from pivot point to short side	
Min. door thickness	40 mm	

DOOR MOVEMENT

Door movement	Self-closing from 125° and -125° to 0°	
	Damper Control - Back-check for damping on opening, soft-close.	

Control can be individually adjusted from the bottom of the door.


System M+ offers absolute control over the movement of pivot doors that weigh 20 to 500 kg and System M does this for doors between 20 and 210 kg. Both systems are equipped with motion technology.



SYSTEM M+ COMPONENTS

1. Ceiling plate (300352)
2. Top pivot (200201)
3. System M+ (100532)
4. Square floor plate (400711) or Round floor plate (400411)

Ceiling plate and floor plate in stainless steel (Series 420) or PVD black. Including mounting set (704000)



SYSTEM M COMPONENTS


1. Ceiling plate (300352)
2. Top pivot (200201)
3. System M (100332)
4. Square floor plate (400711) or Round floor plate (400401)

Ceiling plate and floor plate in stainless steel (Series 420) or PVD black. Including mounting set (704000)

System M+ and System M include the components stated above. Both a square and a round floor plate are available in stainless steel (series 420) and PVD black. The floor plates are made of solid tempered steel and therefore fully corrosion and scratch resistant. The ceiling plate is also available in stainless steel and black to match with the chosen floor plate.


SYSTEM M+ WITH MOTION TECHNOLOGY

DAMPER CONTROL




Damper Control has two functions. The hydraulic back-check protects the pivot door against touching the wall by providing adjustable resistance as the door approaches the 80° position. The closing damping makes the door close smoothly.

30° SPEED CONTROL



30° Speed Control allows you to fine-tune the speed of the pivot door through the last 30° of the closing movement.


LATCH CONTROL



Latch Control provides the ability to adjust the closing speed to latch the door properly. Latch Control enables the door to accelerate in the last 10° to ensure proper latching of the door.

SYSTEM M WITH MOTION TECHNOLOGY


DAMPER CONTROL



Damper Control has two functions. The hydraulic back-check protects the pivot door against touching the wall by providing adjustable resistance as the door approaches the 80° position. The closing damping makes the door close smoothly.


In System M+ and System M the movement of the pivot door is created and controlled by motion technology. System M+ provides extra levels of adjustability. It enables you to fully control the closing movement of the pivot door by means of the 30° Speed Control and Latch Control.

SYSTEM M+ WITH MOTION TECHNOLOGY



- 1 Damper Control** Ensures a smooth and elegant closing movement and protects your door from touching the wall (back-check).
- 2 30° Speed Control** Allows you to determine the speed of the pivot door through the last part of the closing movement.
- L Latch Control** Provides the ability to adjust the pivot hinge to latch the door properly.

SYSTEM M WITH MOTION TECHNOLOGY



- 1 Damper Control** Ensures a smooth and elegant closing movement and protects your door from touching the wall (back-check).

TECHNICAL DRAWING SYSTEM M32+

1. Ceiling plate (300352)
60 x 40 x 17 mm
2. Top pivot (200201)
165 x 32 x 41 mm
3. System M32+ (100532)
294,8 x 32 x 99,6 mm
4. Square floor plate (400711)
80 x 40 x 9 mm

Optional:


Round floor plate (400411)
Ø80 x 9 mm

Downloads

[System M32+ 2D drawing](#)

[System M32+ 3D drawing](#)

[System M32+ BIM model](#)



TECHNICAL DRAWING SYSTEM M42+

1. Ceiling plate (300352)
60 x 40 x 17 mm
2. Top pivot (200201)
165 x 32 x 41 mm
3. System M42+ (100332)
308,2 x 42 x 112,7 mm
4. Square floor plate (400711)
80 x 40 x 9 mm

Optional:


Round floor plate (400411)
Ø80 x 9 mm

Downloads

[System M42+ 2D drawing](#)

[System M42+ 3D drawing](#)

[System M42+ BIM model](#)



TECHNICAL DRAWING SYSTEM M

1. Ceiling plate (300352)
60 x 40 x 17 mm
2. Top pivot (200201)
165 x 32 x 41 mm
3. System M32 (100332)
294,8 x 32 x 99,6 mm
4. Square floor plate (400711)
80 x 40 x 9 mm

Optional:


Round floor plate (400411)
Ø80 x 9 mm

Downloads


[System M 2D drawing](#)

[System M 3D drawing](#)

[System M BIM model](#)




DESIGN OPTIONS SYSTEM M+/M



Square floor plate (400711)
Stainless steel (Series 420)
 80 x 40 x 9 mm
[Download drawing 2D](#)
[Download drawing 3D](#)



Round floor plate (400411)
Stainless steel (Series 420)
 Ø80 x 9 mm
[Download drawing 2D](#)
[Download drawing 3D](#)




Ceiling plate (300352)
Stainless steel (Series 420)
 60 x 40 x 17 mm
[Download drawing 2D](#)
[Download drawing 3D](#)



Square floor plate (400712)
PVD black
 80 x 40 x 9 mm
[Download drawing 2D](#)
[Download drawing 3D](#)



Round floor plate (400412)
PVD black
 Ø80 x 9 mm
[Download drawing 2D](#)
[Download drawing 3D](#)




Ceiling plate (300353)
PVD black
 60 x 40 x 17 mm
[Download drawing 2D](#)
[Download drawing 3D](#)

The floor plate is available in two finishes and shapes: brushed stainless steel (Series 420) and PVD black and can be obtained in a round and a rectangular version. The floor plates by FritsJurgens are made of solid tempered steel and therefore fully scratch resistant. The ceiling plate is available in brushed stainless steel and black as well and can be obtained in the rectangular version only.

SYSTEM M+/M MODEL SELECTOR

www.fritsjurgens.com/M



To ensure the pivot hinge provides the appropriate movement for your door, System M+ is available in seven models and System M in four models suited to the weight and width of the door. There are no limits to the height of the door.

System M+ is suitable for pivot doors covering a range between 20 and 500 kg and is suitable for single- and double-acting doors. When combined with the door frames, the Latch Control ensures the door closes properly.

System M is suitable for pivot doors covering a range between 20 and 210 kg.

EXAMPLE

Use the selection table on the next page.

Specifications door: Width 1600 mm, height 3200 mm, weight 165 kg. The distance between the pivot point of the hinge and the side of the door is 91 mm.

1. Determine the distance of pivot point to the latch side of the door:

$$C \text{ minus } B = A: 1509 \text{ mm}$$

2. Check the door width

$$C = 1600 \text{ mm}$$

3. Fill in the weight

$$KG = 165 \text{ kg}$$

The following system suits this door:


M32(+) SCD

Does your pivot door have other measurements than shown here? Please do not hesitate to contact us. FritsJurgens has an on-site testing facility which enables us to determine whether our systems are suitable for your specific situation.



SYSTEM M+ MODEL SELECTOR


www.fritsjurgens.com/M





SYSTEM M MODEL SELECTOR

www.fritsjurgens.com/M



FRITSJURGENS SYSTEM 3



SYSTEM 3

SYSTEM SPECIFICATIONS

Types	System 3-9016 System 3-9020 System 3-9024 System 3-9028
Dimensions	160 x 32 x 143 mm
Weight	0,75 KG
Material	Stainless Steel Anodized aluminum
Corrosion resistance	EN 1670 - class 5 (norm:0-5)

DOOR SPECIFICATIONS

Door acting	Double-acting 360° rotation
Hold positioning	Hold positions 0°, 90°, 180° and 270°
Weight capacity	40-350 KG
Door width	1000 - 3800 mm
Door height	Unlimited
Pivot point	Middle
Min. door thickness	40 mm


DOOR MOVEMENT

Door movement	Door moves from each 45° angle, in both directions, to a hold position.
---------------	---

SYSTEM 3 COMPONENTS

1. Ceiling plate (300352)
2. Top pivot (200201)
3. System 3 (1001XX)
4. Square floor plate (400601) or Round floor plate (400401)

Ceiling plate and floor plate in stainless steel (Series 420). Including mounting set (701000)



System 3 is very suitable for room dividers and can be applied to create doors that rotate 360°. With this pivot hinge, a door can rotate in a full circle. System 3 has hold positions at every 90° angle and the door always moves to one of the hold positions.

TECHNICAL DRAWING SYSTEM 3

1. Ceiling plate (300352)
60 x 40 x 17 mm
2. Top pivot (200201)
165 x 32 x 41 mm
3. System 3 (1001XX)
160 x 32 x 143 mm
4. Square floor plate (400601)
80 x 40 x 6 mm


Optional:
Round floor plate (400401)
Ø80 x 6 mm

Downloads


[System 3 2D drawing](#)

[System 3 3D drawing](#)

[System 3 BIM model](#)



SYSTEM 3 - MODEL SELECTOR



www.fritsjurgens.com/3

To ensure the pivot hinge provides the appropriate movement for your door, System 3 is available in four models suited to the weight and with of the door. There are no limits to the height of the door.

For the optimal operation of the pivot door in case of particularly high doors and / or pressure differences in the building, select the next heavier System 3 variant, to ensure the closing force.

EXAMPLE

Use the selection table at the next page. Specifications door:

Width 2400 mm, height 3200 mm, weight 165 kg.

1. Check the door width
C = 2400 mm
2. Determine the distance of pivot point to the latch side of the door:
A (C:2) 2400 mm : 2 = 1200 mm
3. Fill in the weight
KG = 165 kg


The following system suits this door:

9024

Does your pivot door have other measurements than shown here? Please do not hesitate to contact us. FritsJurgens has an on-site testing facility which enables us to determine whether our systems are suitable for your specific situation.

SYSTEM 3 MODEL SELECTOR

www.fritsjurgens.com/3



FRITSJURGENS SYSTEM ONE



SYSTEM ONE

SYSTEM SPECIFICATIONS

Type	System One
Dimensions	160 x 32 x 39 mm
Weight	0,36 KG
Material	Stainless Steel Anodized aluminum
Corrosion resistance	EN 1670 - class 5 (norm:0-5)

DOOR SPECIFICATIONS

Door Acting	Double-acting 360° rotation Single-acting 90° rotation
Weight capacity	0-500 KG
Door width	Unlimited
Door height	Unlimited
Pivot point	Min. 91 mm from pivot point to short side
Min. door thickness	40 mm


DOOR MOVEMENT

Door movement	360° free-swinging pivot
---------------	--------------------------

SYSTEM ONE COMPONENTS

1. Ceiling plate (300352)
2. Top pivot (200201)
3. System One (100101)
4. Square floor plate (400601) or Round floor plate (400401)

Ceiling plate and floor plate in stainless steel (Series 420). Including mounting set (701000)





System One excels in its simplicity: one pivot point with a load-bearing capacity of 500 kg. System One allows 360° rotation.

TECHNICAL DRAWING SYSTEM ONE

1. Ceiling plate (300352)
60 x 40 x 17 mm
2. Top pivot (200201)
165 x 32 x 41 mm
3. System One (100101)
160 x 32 x 38 mm
4. Square floor plate (400601)
80 x 40 x 6 mm

Optional:

Round floor plate (400401)
Ø80 x 6 mm



Downloads

[System One 2D drawing](#)

[System One 3D drawing](#)

[System One BIM model](#)

PRESSURE LOAD

AREA


2119 mm²

WEIGHT

500 kg = 4905 N

PRESSURE LOAD

2.31 N/mm²



AS A REFERENCE

AREA


100 mm²

WEIGHT

70 kg = 687 N


PRESSURE LOAD

6.87 N/mm²



A door with a FritsJurgens pivot bears on a 40x80 mm floor plate and produces a pressure load (Fw) of 1.80 N/mm² with a door of 500 kg. For application on your floor we refer to the specifications of the floor manufacturer. As a reference: a woman of circa 70 kg wearing high heels produces a pressure load (Fw) of 6.87 N/mm². All dimensions in mm.

LATERAL FORCE (EXAMPLE)



B=91 MM, WEIGHT DOOR 500 KG


3000	260 N	464 N	669 N	873 N	1078 N	1282 N	1486N
2900	269 N	480 N	692 N	903 N	1115 N	1326 N	1538 N
2800	279 N	498 N	717 N	936 N	1154 N	1373 N	1592 N
2700	289 N	516 N	743 N	970 N	1197 N	1424 N	1651 N
2600	300 N	536 N	772 N	1007 N	1243 N	1479 N	1715 N
2500	312 N	557 N	803 N	1048 N	1293 N	1538 N	1784 N
2400	325 N	580 N	836 N	1091 N	1347 N	1602 N	1858 N
2300	339 N	606 N	872 N	1139 N	1405 N	1672 N	1939 N
2200	355 N	633 N	912 N	1191 N	1469 N	1748 N	2027 N
2100	371 N	663 N	955 N	1247 N	1539 N	1831 N	2123 N
2000	390 N	697 N	1003 N	1310 N	1616 N	1923 N	2229 N
	500	750	1000	1250	1500	1750	2000

B=1/5 WIDTH DOOR, WEIGHT DOOR 500 KG

3000	245 N	368 N	491 N	613 N	736 N	858 N	981 N
2900	254 N	381 N	507 N	634 N	761 N	888 N	1015 N
2800	263 N	394 N	526 N	657 N	788 N	920 N	1051 N
2700	273 N	409 N	545 N	681 N	818 N	954 N	1090 N
2600	283 N	425 N	566 N	708 N	849 N	990 N	1132 N
2500	294 N	442 N	589 N	736 N	883 N	1030 N	1177 N
2400	307 N	460 N	613 N	766 N	920 N	1030 N	1226 N
2300	320 N	480 N	640 N	800 N	960 N	1120 N	1280 N
2200	334 N	502 N	669 N	836 N	1003 N	1171 N	1338 N
2100	350 N	526 N	701 N	876 N	1051 N	1226 N	1401 N
2000	368 N	552 N	736 N	920 N	1104 N	1288 N	1472 N
	500	750	1000	1250	1500	1750	2000

The minimum distance for B is 91 mm. See above for two examples. As a result of the placement of System 3 or System One in the middle of the door, there is no extra lateral force (f_{rad}) on the floor and ceiling.

ACCESSORIES: CABLE GROMMET



The Cable Grommet is an addition to the existing FritsJurgens top pivot range and enables wiring in the door. This top pivot contains an integrated cable grommet of $\varnothing 7.5$ mm. This version of the top pivot is available with every FritsJurgens system and replaces the standard delivered top pivot and ceiling plate within a complete set.


CABLE GROMMET

SPECIFICATIONS

Types	FritsJurgens top pivot - cable entry (200211) FritsJurgens ceiling plate - cable entry (300361)
Dimensions	165 x 32 x 41 mm

FOR TYPES OF DOORS

Door acting	Double-acting Single-acting
Weight capacity	0-500 KG
Door width	Unlimited
Door height	Unlimited
Pivot point	Min. 91 mm from pivot point to short side
Min. door thickness	40 mm



CABLE GROMMET COMPONENTS

1. Top pivot - cable entry
2. Ceiling plate - cable entry

Downloads





[Top pivot - cable entry 2D drawing](#)

[Top pivot - cable entry 3D drawing](#)


[Ceiling plate - cable entry 2D drawing](#)

[Ceiling plate - cable entry 3D drawing](#)

INSTALLATION



ACCESSORIES: FLUSH



The Flush consists of two strong magnets. These are mounted in the bottom side of the pivot door and the adjacent wall. The Flush hereby strengthens the 0° position of every pivot door, regardless its size or weight. The pivot door is always perfectly in line with the adjacent wall or door. A seamless junction, fully 'flush'.


FLUSH

SPECIFICATIONS

Types	FritsJurgens Flush 707001 (stainless steel) FritsJurgens Flush 707002 (black)
	Optional: Forstner drill bit Ø22 mm (with clamping ring)
Dimensions	50 x 22 x 15 mm

FOR TYPES OF DOORS

Door acting	Double-acting Single-acting
Weight capacity	0-500 KG
Door width	Unlimited
Door height	Unlimited
Pivot point	Min. 91 mm from pivot point to short side
Min. door thickness	40 mm



FLUSH COMPONENTS

1. Magnets (2x)
2. Cover plates (2x)
3. Optional: drill bit Ø22 mm


Cover plates in stainless steel or black

Downloads




[Flush 2D drawing](#)

[Flush 3D drawing](#)

INSTALLATION




Recommended for use:
Forstner drill bit Ø22 mm
Optional to order



Door seam <---->
3.0 mm - 6.0 mm

HEXAGON GUIDE



The Hexagon Guide can ease the installation of the pivot door. The minimum distance from the pivot point to the edge of the door is 91 mm and the maximum distance is the middle of the door width. In case the pivot point is more than 280 mm from the edge of the door we offer the Hexagon Guide to ease the installation.

HEXAGON GUIDE

SPECIFICATIONS

Types	FritsJurgens Hexagon Guide - 1 m (706000) FritsJurgens Hexagon Guide - 2 m (706200)
Dimensions	1M: 998 x 31.5 x 44 mm 2M: 1998 x 31.5 x 44 mm


FOR TYPES OF DOORS

Door acting	Double-acting Single-acting
Weight capacity	0-500 KG
Door width	Unlimited
Door height	Unlimited
Pivot point	Min. 280 mm from pivot point to short side
Min. door thickness	40 mm




HEXAGON GUIDE COMPONENTS

1. Hexagon Guide
2. Hexagon key



Downloads

[Hexagon guide 1 m 2D drawing](#)
[Hexagon guide 1 m 3D drawing](#)
[Hexagon guide 2 m 2D drawing](#)
[Hexagon guide 2 m 3D drawing](#)


INSTALLATION



AXLE WRENCH



When installing a door fitted with System M, it is very important that the door is installed in its open position. This can be accomplished by using the Axle Wrench to rotate the oval spindle in the bottom of the System M 90°, pointing the arrow toward the direction the door will be opening (0° position). In case of frequent use it is possible to mount the floor plate (art. 400701) on the Axle Wrench.


AXLE WRENCH

SPECIFICATIONS




Types	FritsJurgens Axle Wrench (500503)
Dimensions	400 x 36 x 3 mm

AXLE WRENCH COMPONENTS

1. Axle Wrench
2. 2x M6 fixing screws (in case of frequent use it is possible to mount the floor plate on the Axle Wrench).



INSTALLATION



FritsJurgens®

FRITSJURGENS INTERNATIONAL

A. Einsteinlaan 1
9615 TE Kolham
The Netherlands
+31 598 343 410
info@fritsjurgens.com

FRITSJURGENS ITALY

Via Marsilio Ficino 22
50132 Firenze
Italy
+39 055 064 0290
info@fritsjurgens.com

FRITSJURGENS CHINA

上海市长寿路360号源达大厦1508室
360 Changshou Road, Room 1508, Shanghai
China
+86 138 1692 5021
info@fritsjurgens.com

www.fritsjurgens.com/question

www.fritsjurgens.com/web